

ELECTRONIC TUBE REFERENCE

8B08ZB

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

High-resolution 8.5-inch rectangular radar display CRT with magnetic focusing and deflection and a metal-backed screen for detailed radar presentation.

GENERAL CHARACTERISTICS

BASE DESIGNATION	B12A	BASE PINS	—
NOMINAL HEATER	6.3 V / 300 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	15000 V
<i>Promoted fields were populated only where the Ferranti sheet maps cleanly to the locked schema; additional ratings and operating values are retained in TUBE_SECTION_PARAMETER.</i>	

High-resolution 8.5-inch rectangular radar display CRT with magnetic focus and deflection and metal-backed screen.

SOURCE OPERATING CONDITIONS

1963 Ferranti

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1963 FERRANTI

Section 1 · Cathode Ray

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
First-anode voltage maximum	600 V	—
Second-anode voltage minimum	9000 V	—
First-anode voltage	300 V	—
Second-anode voltage	15000 V	—
Visual cutoff grid voltage minimum	-90 V	—
Visual cutoff grid voltage maximum	-30 V	—
Average modulation drive for 50uA beam current	20 V	—

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Cathode-to-all capacitance maximum	8 pF	—
Grid-to-all capacitance maximum	8 pF	—