



ELECTRONIC TUBE REFERENCE

920

Specialized - Photo Tube electronic tube

CONSOLIDATED TECHNICAL DATA

2 SECTIONS

CONSTRUCTION

PHOTOEMISSIVEDETECTOR-
PHOTOEMISSIVEDETECTOR

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Indirect; cold cathode	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION0 PhotoemissiveDetector

No fixed ratings recorded.

Photoemissive detector; manufacturer maximum ratings and spectral characteristics in datasheet.

SECTION1 PhotoemissiveDetector

No fixed ratings recorded.

Second independent S-2 gas phototube unit; maximum anode supply 90 V.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

9999 Mixed D 1000

Published test conditions and operating points. Values on this page are preserved as reported by this source.

9999 MIXED D 1000

Section 0 · PhotoemissiveDetector

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum plate voltage	90 V	Unit 1 maximum anode supply

9999 MIXED D 1000

Section 1 · PhotoemissiveDetector

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum plate voltage	90 V	Unit 2 maximum anode supply