

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Indirect; cold cathode	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION0	PhotoemissiveDetector
<i>No fixed ratings recorded.</i>	
<i>Photoemissive detector; manufacturer maximum ratings and spectral characteristics in datasheet.</i>	



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

9999 Mixed D 1000

Published test conditions and operating points. Values on this page are preserved as reported by this source.

9999 MIXED D 1000

Section 0 · PhotoemissiveDetector

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum plate voltage	250 V	Maximum anode supply

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Wavelength of maximum response	340 nm	S-5 peak response

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker