



ELECTRONIC TUBE REFERENCE

9Q2051

Rectifier - Half Wave electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

RECTIFIER

Hot-cathode mercury-vapor half-wave rectifier for industrial high-voltage supplies, providing approximately 21 kV inverse-voltage capability and ampere-class rectified output.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	5 V / 12 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Rectifier	
PEAK INVERSE VOLTAGE	21000 V
NOMINAL OUTPUT CURRENT	2.5 A
PEAK FORWARD CURRENT	10 A
<i>Published ratings and characteristics promoted where clearly stated; identical repeated sections compressed when applicable.</i>	

Mercury-vapor hot-cathode high-voltage rectifier for industrial rectifier equipment.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1953 RFT Rundfunk Technik

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1953 RFT RUNDFUNK TECHNIK

Section 1 · Rectifier

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater or filament voltage	5 V	Published nominal value
Heater or filament current	12 A	Published nominal value

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker