



ELECTRONIC TUBE REFERENCE

A1834

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA
2 SECTIONS
CONSTRUCTION
TRIODE

High-mu planar transmitting triode designed for grounded-grid microwave oscillator and amplifier service. Its low-inductance metal-ceramic construction and very low interelectrode capacitance support operation well into the microwave frequency range.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 2.5 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
TRANSCONDUCTANCE	0.0075 S
MAXIMUM PLATE VOLTAGE	250 V
MAXIMUM PLATE DISSIPATION	13 W
Representative section row for two equivalent triode systems. Published maximum ratings and characteristics audited; remaining useful numerical data retained in TUBE_SECTION_PARAMETER.	

The A1834 is an indirectly heated dual triode intended for DC-amplifier and scanning-booster service, with two equivalent triode systems.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1955 Marconi

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1955 MARCONI

Section 1 · Triode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater voltage	6.3 V	Published heater rating.
Heater current	2.5 A	Published heater rating.
Peak heater-cathode voltage	300 V	Maximum rating.
Plate voltage	250 V	Maximum per triode system.
Plate dissipation	13 W	Maximum per triode system.
Transconductance	7500 μ S	Characteristic per triode system.
Scanning-booster peak inverse voltage	17000 V	Maximum scanning-booster rating; pulse duration limited to 10 μ s and 15% of scanning cycle.

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker