



ELECTRONIC TUBE REFERENCE

A3064_GEC

Voltage - Pentode electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

PENTODE

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 300 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Pentode	
TRANSCONDUCTANCE	0.00762 S
MAXIMUM PLATE VOLTAGE	300 V
MAXIMUM SCREEN VOLTAGE	300 V
MAXIMUM PLATE DISSIPATION	2.5 W
MAXIMUM SCREEN DISSIPATION	0.8 W



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

9999 Mixed G 2000

Published test conditions and operating points. Values on this page are preserved as reported by this source.

9999 MIXED G 2000

Section 1 · Pentode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Screen Voltage	250 V	—
Plate Voltage	250 V	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker