ELECTRONIC TUBE REFERENCE

A410

Voltage - Triode (single) electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
TRIODE

Low-filament-current directly heated receiving triode for detector and high- or low-frequency amplification from a four-volt accumulator.

General characteristics

BASE DESIGNATION	A32	**BASE PINS**	4
NOMINAL HEATER	3.7 V / 60 mA	**PARALLEL HEATER**	– / –
HEATING	Direct	**SERIES OPERATION**	Not specified
CATHODE ARRANGEMENT	Separate cathodes	**SECTION CONSTRUCTION**	Similar

Section ratings

SECTION1 Triode

PLATE RESISTANCE	22000 Ω
TRANSCONDUCTANCE	0.00045 S
AMPLIFICATION FACTOR	10
MAXIMUM PLATE VOLTAGE	100 V

Low-filament-current directly heated receiving triode for detection and high- or low-frequency amplification from a 4 V accumulator.

Low-filament-current directly heated receiving triode for detection and high- or low-frequency amplification from a 4 V accumulator.

SOURCE OPERATING CONDITIONS

1999 Philips 0-D

SOURCE PDF

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1999 PHILIPS 0-D

Section 1 · Triode

CHARACTERISTIC		
PARAMETER	**PUBLISHED VALUE**	**CONDITION / NOTE**
Saturation current	**10 mA**	—

Tube Tinker

An independent reference for electronic tubes, vacuum tubes, and their source documents.

Catalog Tube types Full books Blog Feedback & corrections

© 2026 Tube Tinker