

ELECTRONIC TUBE REFERENCE

A4414W

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

European rectangular monochrome television picture tube with electrostatic focusing, magnetic deflection, and an aluminized or metal-backed screen. Manufacturer documentation supports direct-view receiver service with wide-angle deflection and compact cabinet geometry.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 300 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	20000 V
Published ratings and characteristics promoted where clearly stated; identical repeated sections compressed when applicable.	

44 cm 114-degree self-protected monochrome television picture tube with tinted aluminized screen.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1968 Mazda Belvu

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1968 MAZDA BELVU

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater or filament voltage	6.3 V	Published nominal value
Heater or filament current	300 mA	Published nominal value
Screen diagonal	44 cm	Published
Deflection angle	114 deg	Published