



ELECTRONIC TUBE REFERENCE

A50130W

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

50 cm-class monochrome television picture tube for high-voltage direct-view service, with manufacturer-defined magnetic deflection, focusing, screen, and beam-control characteristics.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 300 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	22000 V
<i>Published ratings and characteristics promoted where clearly stated; identical repeated sections compressed when applicable.</i>	

50 cm 114-degree self-protected monochrome television picture tube with tinted aluminized screen.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1968 Mazda Belvu

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1968 MAZDA BELVU

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater or filament voltage	6.3 V	Published nominal value
Heater or filament current	300 mA	Published nominal value
Screen diagonal	50 cm	Published
Deflection angle	114 deg	Published

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker