



ELECTRONIC TUBE REFERENCE

AG872A

Rectifier - Half Wave electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
RECTIFIER

AEG directly heated mercury-vapor half-wave rectifier for high-voltage power conversion, providing approximately 10 kV inverse-voltage capability and ampere-class output.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	5 V / 7 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Rectifier	
PEAK INVERSE VOLTAGE	10000 V
NOMINAL OUTPUT CURRENT	1.25 A
PEAK FORWARD CURRENT	5 A

Directly heated mercury-vapour rectifier.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1953 AEG

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1953 AEG

Section 1 · Rectifier

CONSTRUCTION

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Filling	Mercury vapour	—

CHARACTERISTIC

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Ignition voltage maximum	30 V	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker