



ELECTRONIC TUBE REFERENCE

AM1

Tuning Indicator electronic tube

CONSOLIDATED TECHNICAL DATA

2 SECTIONS

CONSTRUCTION

TRIODE-TUNING INDICATOR

Four-volt tuning-cross visual indicator producing a fluorescent cross-pattern controlled by signal-derived voltage for accurate receiver tuning.

GENERAL CHARACTERISTICS

BASE DESIGNATION	P26	BASE PINS	—
NOMINAL HEATER	4 V / 300 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Dissimilar

SECTION RATINGS

SECTION1 Tuning Indicator

MAXIMUM PLATE VOLTAGE	250 V
-----------------------	-------

Visual tuning-cross indicator.

SECTION2 Triode

No fixed ratings recorded.

4 V tuning-cross visual indicator. Electrical ratings and operating characteristics were extracted from the supplied 4-volt valve data table, including the published heater data and available section-level values.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1938 Philips Miniwatt Vacuum Tube Catalog

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1938 PHILIPS MINIWATT VACUUM TUBE CATALOG

Section 1 · Tuning Indicator

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Anode voltage	250 V	—
Anode current	0.095 mA	—
Maximum indicated current	0.021 mA	—

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Grid control voltage	-54 V	—
Sensitivity	9.5	—