

ELECTRONIC TUBE REFERENCE

ASG5007

Specialized - Thyatron electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
THYRATRON

Mercury-vapor thyatron for high-voltage controlled rectification and industrial switching. Its heavy filament supports substantial grid-triggered current.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	3
NOMINAL HEATER	5 V / 14 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Thyatron	
MAXIMUM PLATE VOLTAGE	26000 V
MAXIMUM CATHODE CURRENT	2.5 A
Mercury-vapor thyatron; canonical SectionType has no Thyatron value, so Other is used.	

A directly heated mercury-vapor thyatron with control grid, intended primarily for high-voltage half-wave rectification and also for switching and control in industrial regulating equipment.



SOURCE OPERATING CONDITIONS

1953 RFT Rundfunk Technik

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1953 RFT RUNDFUNK TECHNIK

Section 1 · Thyatron

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum peak anode voltage	26 kV	—
Maximum cathode current	2.5 A	—
Maximum surge current	10 A	—
Maximum grid resistance	30 kOhm	—
Maximum positive grid voltage	600 V	—
Minimum negative grid voltage	600 V	—
Minimum warmup time	60 s	After transport

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker