



ELECTRONIC TUBE REFERENCE

B2006

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Philips power triode with a published 5-watt output operating point, meeting the project's minimum power-category threshold.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	20 V / 180 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
PLATE RESISTANCE	4000 Ω
TRANSCONDUCTANCE	0.016 S
AMPLIFICATION FACTOR	6
MAXIMUM PLATE VOLTAGE	200 V
MAXIMUM CATHODE CURRENT	30 mA
<i>Published table ratings and electrical characteristics reviewed; ambiguous cells were not inferred.</i>	

B2006 is listed in the supplied tube table as a power triode. Published electrical values were transcribed from its target row.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1938 Philips Miniwatt Vacuum Tube Catalog

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1938 PHILIPS MINIWATT VACUUM TUBE CATALOG

Section 1 · Triode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum plate voltage	200 V	Published table rating
Plate voltage	200 V	Published operating point
Control-grid bias	18 V	Published operating point
Plate current	15 mA	Published operating point
Power output	5 W	Published operating point

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate resistance	4000 ohm	Published table characteristic
Transconductance	16000 μ S	Published table characteristic
Amplification factor	6	Published table characteristic
Heater/filament voltage	20 V	Published heater/filament rating
Heater/filament current	180 mA	Published heater/filament rating



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1999 Philips 0-D

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1999 PHILIPS 0-D

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Normal plate current	15 mA	—
Maximum cathode current	30 mA	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#)[Tube types](#)[Full books](#)[Blog](#)[Feedback & corrections](#)

© 2026 Tube Tinker