

Varian/Bomac BL-625 manufacturer designation for JEDEC 6805, a double TR microwave switching tube for radar duplexing and receiver protection.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1	MicrowaveTRSwitch
No fixed ratings recorded.	

Varian/Bomac BL-625 manufacturer designation for JEDEC 6805 double TR tube.

SOURCE OPERATING CONDITIONS

1953 Varian Assoc

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1953 VARIAN ASSOC

Section 1 · Microwave TR Switch

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Flat leakage power maximum	40 mW	—
Transmitter peak power maximum	200 kW	—
Transmitter average power maximum	200 W	—
Ignitor current maximum	200 uA	—

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Recovery time maximum	10 us	At 200 kW Peak

CONSTRUCTION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Device type	Double broadband TR tube	—