



ELECTRONIC TUBE REFERENCE

BY189A

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Radio-frequency transmitting triode with grid terminals arranged for cathode-drive operation in RF power-amplifier service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
TRANSCONDUCTANCE	0.275 S
AMPLIFICATION FACTOR	34
MAXIMUM PLATE VOLTAGE	15000 V

R.f. transmitting triode with grid terminals suitable for cathode-drive operation.



SOURCE OPERATING CONDITIONS

1971 English Electric Valve

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1971 ENGLISH ELECTRIC VALVE

Section 1 · Triode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Anode dissipation BR189	27 kW	BR189
Output power class C telegraphy	30 kW	ClassC

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker