ELECTRONIC TUBE REFERENCE

C22SS1B

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
CATHODERAY

Special-purpose cathode-ray instrument tube from the Standard Telephones and Cables family, with screen variant and electron-optical characteristics designated by the C22SS1B suffix.

General characteristics

BASE DESIGNATION	—	**BASE PINS**	—
NOMINAL HEATER	2 V / 1.9 A	**PARALLEL HEATER**	— / —
HEATING	Indirect	**SERIES OPERATION**	Not specified
CATHODE ARRANGEMENT	Separate cathodes	**SECTION CONSTRUCTION**	Similar

Section ratings

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	5000 V
High-vacuum cathode-ray tube.	

High-vacuum blue-screen cathode-ray tube.

SOURCE OPERATING CONDITIONS

1946 Standard Telephone and Cables

SOURCE PDF

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1946 STANDARD TELEPHONE AND CABLES

Section 1 · Cathode Ray

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Interelectrode capacitances published	1	See source table for individual capacitances

SOURCE DATA APPENDIX

SOURCE OPERATING CONDITIONS

1947 Standard Valves

SOURCE PDF

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1947 STANDARD VALVES

Section 1 · Cathode Ray

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum anode voltage	5 kV	—
Maximum screen input power	0.01 W/cm2	—
Third anode voltage	5 kV	—
First anode voltage	150 V	—

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
X sensitivity	600 mm/V	V = final anode voltage
Y sensitivity	700 mm/V	V = final anode voltage

An independent reference for electronic tubes, vacuum tubes, and their source documents.

Catalog Tube types Full books Blog Feedback & corrections

© 2026 Tube Tinker