



ELECTRONIC TUBE REFERENCE

C28GS1G

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

CATHODERAY

Special-purpose cathode-ray instrument tube from the Standard Telephones and Cables family, with screen variant and electron-optical characteristics designated by the C28GS1G suffix.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	9
NOMINAL HEATER	0.75 V / —	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	1500 V
<i>Gas-focused CRT; green screen.</i>	

A gas-focused cathode-ray tube family with blue, green, and delay screen versions and electrostatic deflection.



SOURCE OPERATING CONDITIONS

1946 Standard Telephone and Cables

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1946 STANDARD TELEPHONE AND CABLES

Section 1 · Cathode Ray

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Interelectrode capacitances published	1	See source table for individual capacitances



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1947 Standard Valves

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1947 STANDARD VALVES

Section 1 · Cathode Ray

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Filament current	700 mA–1.1 A	—
Anode voltage	350–1500 V	—
Normal anode voltage	500 V	—
Shield voltage	0–50 V	—

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Sensitivity	580 mm/V	V = anode voltage

DIMENSIONS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Effective screen diameter	6.5 in	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker