



ELECTRONIC TUBE REFERENCE

CK1359P25A

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

CATHODERAY

Raytheon radar cathode-ray tube with electrostatic focusing, magnetic deflection, and a P25 screen. This family is designed for direct radar indication, with metallized or filter-face construction on applicable variants.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	16500 V
<i>Published ratings and characteristics promoted where clearly stated.</i>	

16-inch electrostatic-focus, magnetic-deflection radar cathode-ray tube with gray filter faceplate and metallized P25 screen.



SOURCE OPERATING CONDITIONS

1938 Raytheon

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1938 RAYTHEON

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater or filament voltage	6.3 V	Published nominal value
Heater or filament current	600 mA	Published nominal value
Screen phosphor	P25	Published family variant
Deflection angle	52 deg	Published approximate value

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker