

ELECTRONIC TUBE REFERENCE

CK1366

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Three-inch printer-type cathode-ray tube with a single-row electrostatic printing element. Raytheon designed it for high-speed electronic printing equipment rather than conventional visual display.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	25000 V
Published ratings and characteristics promoted where clearly stated.	

3-inch printer-type cathode-ray tube with single-row electrostatic printing element for high-speed label-printing equipment.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1938 Raytheon

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1938 RAYTHEON

Section 1 · Cathode Ray

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater or filament voltage	6.3 V	Published nominal value
Heater or filament current	600 mA	Published nominal value
Printing wires per inch	250 1/in	single-row

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Collector operating voltage	20000 V	Published

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker