

ELECTRONIC TUBE REFERENCE

CK5751

Voltage - Dual Triode (similar) electronic tube

CONSOLIDATED TECHNICAL DATA
2 SECTIONS
CONSTRUCTION
TRIODE-TRIODE

Reliable miniature dual triode listed by Raytheon for voltage-amplifier service, with published characteristics specified independently for each section.

GENERAL CHARACTERISTICS

BASE DESIGNATION	9W	BASE PINS	9
NOMINAL HEATER	12.6 V / 175 mA	PARALLEL HEATER	6.3 V / 350 mA
HEATING	Indirect	SERIES OPERATION	Capable
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
PLATE RESISTANCE	58000 Ω
TRANSCONDUCTANCE	0.0012 S
AMPLIFICATION FACTOR	70
Reliable miniature dual triode; published characteristics are per section.	

SECTION2 Triode	
PLATE RESISTANCE	58000 Ω
TRANSCONDUCTANCE	0.0012 S
AMPLIFICATION FACTOR	70
Second physical triode section; electrically identical twin section.	

CK5751 is a DualTriode tube listed by Raytheon for voltage amplifier service. Reliable miniature dual triode; published characteristics are per section.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

195X Raytheon Special Purpose Tubes

Published test conditions and operating points. Values on this page are preserved as reported by this source.

195X RAYTHEON SPECIAL PURPOSE TUBES

Section 1 · Triode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate voltage	250 V	EachUnit
Control-grid voltage	-3 V	EachUnit
Plate current	1 mA	EachUnit

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker