

ELECTRONIC TUBE REFERENCE

CK5884

Voltage - Dual Tetrode electronic tube

CONSOLIDATED TECHNICAL DATA
2 SECTIONS
CONSTRUCTION
TETRODE-TETRODE

Directly heated subminiature double tetrode designed for electrometer service, with nominal control-grid current around 10^{-14} ampere.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	1.25 V / 10 mA	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Tetrode

No fixed ratings recorded.

Directly heated subminiature double tetrode for electrometer service; nominal control-grid current is 1×10^{-14} A.

SECTION2 Tetrode

No fixed ratings recorded.

Second physical electrometer tetrode restored under current section policy.

CK5884 is a DualTetrode tube listed by Raytheon for electrometer service. Directly heated subminiature double tetrode for electrometer service; nominal control-grid current is 1×10^{-14} A.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

195X Raytheon Special Purpose Tubes

Published test conditions and operating points. Values on this page are preserved as reported by this source.

195X RAYTHEON SPECIAL PURPOSE TUBES

Section 1 · Tetrode

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Nominal control-grid current	0.000000000001 mA	Electrometer

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker