

ELECTRONIC TUBE REFERENCE

CRM71

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Mazda CRM-series cathode-ray tube documented for television or oscillographic display service. The available source does not justify selecting one exclusive application, so it remains a general display CRT.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	2 V / 1.4 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	4000 V
CRT electrical section; anode-2/accelerating voltage promoted where clearly published.	

CRM71 cathode-ray tube for television or oscillographic display service.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1960 Mazda

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 MAZDA

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Typical anode voltage	3500 V	—