



ELECTRONIC TUBE REFERENCE

CV2518

Rectifier - Half Wave electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
RECTIFIER

Directly heated xenon-filled half-wave rectifier for substantial high-voltage supplies. Its heavy filament and gas-assisted conduction provide ampere-class current at multi-kilovolt voltage.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	4
NOMINAL HEATER	5 V / 7.1 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Rectifier	
PEAK INVERSE VOLTAGE	10000 V
NOMINAL OUTPUT CURRENT	1.25 A
PEAK FORWARD CURRENT	5 A
FORWARD VOLTAGE DROP	16 V
<i>Explicit alias/co-designation; values duplicated from the same approved source.</i>	

Xenon-filled half-wave rectifier.

SOURCE OPERATING CONDITIONS

1946 Standard Telephone and Cables

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1946 STANDARD TELEPHONE AND CABLES

Section 1 · Rectifier

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Supply frequency	50 Hz	ChokeInputFilter
Minimum cathode heating time	30 s	—
Maximum fault anode current	50 A	—
Maximum fault-current duration	0.1 s	—

SOURCE OPERATING CONDITIONS

1971 English Electric Valve

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1971 ENGLISH ELECTRIC VALVE

Section 1 · Rectifier

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Fault anode current	50 A	0.1s max

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

