ELECTRONIC TUBE REFERENCE

D14172GH

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
CATHODERAY

General characteristics

BASE DESIGNATION	_	**BASE PINS**	_
NOMINAL HEATER	6.3 V / 300 mA	**PARALLEL HEATER**	– / –
HEATING	Indirect	**SERIES OPERATION**	Not specified
CATHODE ARRANGEMENT	Separate cathodes	**SECTION CONSTRUCTION**	Similar

Section ratings

SECTION0 Cathode Ray

No fixed ratings recorded.

GH oscilloscope CRT, maximum final anode 4 kV.

SOURCE OPERATING CONDITIONS

9999 Mixed D 2000

SOURCE PDF

Published test conditions and operating points. Values on this page are preserved as reported by this source.

9999 MIXED D 2000

Section 0 · Cathode Ray

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater/filament current	300 mA	Heater current
Heater/filament current	300 mA	Heater current
Maximum plate voltage	4000 V	Maximum fourth-anode voltage

Tube Tinker

An independent reference for electronic tubes, vacuum tubes, and their source documents.

Catalog Tube types Full books Blog Feedback & corrections

© 2026 Tube Tinker