



ELECTRONIC TUBE REFERENCE

DAC41W

Voltage - Triode (with diode, heptode or hexode) electronic tube

CONSOLIDATED TECHNICAL
DATA

2 SECTIONS
CONSTRUCTION
DIODE-TRIODE

German combined diode-triode receiving valve with published operating data and limiting ratings for detector and amplifier service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	1.2 V / 200 mA	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
MAXIMUM PLATE VOLTAGE	135 V
MAXIMUM PLATE DISSIPATION	1 W
MAXIMUM CATHODE CURRENT	1 mA
<i>Published ratings and characteristic constants promoted where applicable.</i>	

SECTION2 Diode	
<i>No fixed ratings recorded.</i>	
<i>Missing physical diode section added in approved section-structure reconciliation.</i>	

DAC41W: combined diode-triode valve with published operating data and limiting ratings. The approved German-language datasheet was translated and interpreted by technical meaning.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

194X Wehrmacht Rohren

Published test conditions and operating points. Values on this page are preserved as reported by this source.

194X WEHRMACHT ROHREN

Section 1 · Triode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater current	200 mA	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum anode voltage	135 V	—
Maximum anode dissipation	1 W	—
Maximum cathode current	1 mA	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker