



ELECTRONIC TUBE REFERENCE

DCG55000EG

Rectifier - Half Wave electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
RECTIFIER

Directly heated mercury-vapor half-wave industrial rectifier for high-voltage power conversion, using low arc voltage to provide efficient ampere-class DC output.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	5 V / 17 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Rectifier	
PEAK INVERSE VOLTAGE	13000 V
NOMINAL OUTPUT CURRENT	1.5 A
PEAK FORWARD CURRENT	6 A
FORWARD VOLTAGE DROP	12 V
WARM-UP TIME	30 s
<i>Single-anode mercury-vapour industrial rectifier.</i>	

DCG55000EG is a Rectifier device in the supplied Philips industrial literature. Single-anode mercury-vapour industrial rectifier.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1963 Philips Electron Tubes Handbook V4

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1963 PHILIPS ELECTRON TUBES HANDBOOK V4

Section 1 · Rectifier

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Peak inverse voltage	13 kV	Condition1
Maximum average current	1.5 A	Condition1
Maximum peak current	6 A	Condition1
Peak inverse voltage	10 kV	Condition2
Maximum average current	1.5 A	Condition2
Peak inverse voltage	5 kV	Condition3
Maximum average current	1.75 A	Condition3
Maximum peak current	7 A	Condition3
Maximum surge current	40 A	—

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Arc voltage drop	12 V	—



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1999 Philips 0-D

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1999 PHILIPS 0-D

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater voltage	5 V	—
Heater current	17 A	—
Maximum peak inverse voltage	13000 V	—
Maximum rectified current	1.5 A	—
Maximum peak forward current	6 A	—
Maximum surge current	40 A	—
Minimum warm-up time	30 s	—

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Forward voltage drop	12 V	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#)[Tube types](#)[Full books](#)[Blog](#)[Feedback & corrections](#)

© 2026 Tube Tinker