



ELECTRONIC TUBE REFERENCE

DE2HF_GEV

Voltage - Triode (single high frequency) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Geco early directly heated HF receiving triode, filament 1.8-2 V at 0.12 A, amplification factor 12, internal resistance 45 kohms.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / 120 mA	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
PLATE RESISTANCE	45000 Ω
AMPLIFICATION FACTOR	12



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

9999 Mixed D 2000

Published test conditions and operating points. Values on this page are preserved as reported by this source.

9999 MIXED D 2000

Section 1 · Triode

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate Voltage	80 V	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker