

ELECTRONIC TUBE REFERENCE

DLS17

Specialized - Switching Tube electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
THERMALDELAYSWITCH

Vacuum thermal-delay switch. Controlled heater warm-up actuates internal contacts after a time interval for sequencing and protective control.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	4 V / 1.5 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 ThermalDelaySwitch
No fixed ratings recorded.

Vacuum thermal delay switch.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1960 Mazda

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 MAZDA

Section 1 · ThermalDelaySwitch

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Minimum delay time	30 s	—
Maximum delay time	90 s	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum switch current at 250 V	6 A	—
Maximum switch current at 1000 V	200 mA	—