



ELECTRONIC TUBE REFERENCE

DVSPEN

Voltage - Pentode Remote Cutoff (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

PENTODE

Cossor pentode documented with construction, technical data, operating recommendations, and application notes. Available extracted material does not establish a stronger functional identity than its existing variable-gain pentode grouping.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	7
NOMINAL HEATER	16 V / 250 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Pentode	
TRANSCONDUCTANCE	0.002 S
MAXIMUM PLATE VOLTAGE	200 V
<i>Published ratings/characteristics promoted from the approved datasheet.</i>	

DVSPEN: Cossor pentode valve. The complete Cossor sheet was read for construction, technical data, operating recommendations, and application notes.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1936 Cossor Valve Manual

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1936 COSSOR VALVE MANUAL

Section 1 · Pentode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater/filament voltage	16 V	—
Control characteristic	Variable-mu	—
Intended service	High-frequency amplifier	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum anode voltage	200 V	—



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

193X Cossor

Published test conditions and operating points. Values on this page are preserved as reported by this source.

193X COSSOR

Section 1 · Pentode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Mutual Conductance	200000 μ S	Published technical-data value

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

