

ELECTRONIC TUBE REFERENCE

E2668B1

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
IMAGESTORAGE

Toshiba six-inch BHD direct-view storage CRT, separate writing heater 6.3 V 0.6 A and reading heater 6.5 V 0.6 A.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1	ImageStorage
MAXIMUM PLATE VOLTAGE	4500 V



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

9999 Mixed I 1000

Published test conditions and operating points. Values on this page are preserved as reported by this source.

9999 MIXED I 1000

Section 1 · ImageStorage

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate Voltage	3500 V	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker