



ELECTRONIC TUBE REFERENCE

ECC83MG

Voltage - Dual Triode (similar) electronic tube

CONSOLIDATED TECHNICAL DATA

2 SECTIONS

CONSTRUCTION

TRIODE-TRIODE

High-mu twin triode for low-level audio voltage amplification, a modern ECC83-family variant intended for preamplifier and other high-gain small-signal applications.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	9
NOMINAL HEATER	12.6 V / 150 mA	PARALLEL HEATER	6.3 V / 300 mA
HEATING	Indirect	SERIES OPERATION	Capable
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
PLATE RESISTANCE	62500 Ω
TRANSCONDUCTANCE	0.0016 S
AMPLIFICATION FACTOR	100
MAXIMUM PLATE VOLTAGE	300 V
MAXIMUM PLATE DISSIPATION	1 W
MAXIMUM CATHODE CURRENT	8 mA
Representative section for two electrically identical sections.	

SECTION2 Triode	
PLATE RESISTANCE	62500 Ω
TRANSCONDUCTANCE	0.0016 S
AMPLIFICATION FACTOR	100
MAXIMUM PLATE VOLTAGE	300 V
MAXIMUM PLATE DISSIPATION	1 W
MAXIMUM CATHODE CURRENT	8 mA
<i>Second physical triode restored.</i>	

High-mu audio-frequency double triode in MG construction; also designated ECC83MG. Printed co-designation record duplicated from 12AX7MG.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

2026 JJ Electronic

Published test conditions and operating points. Values on this page are preserved as reported by this source.

2026 JJ ELECTRONIC

Section 1 · Triode

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
R _g	2.2 MΩ	Published value

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
U _a	250 V	Published value
U _g	-2 V	Published value
I _a	1.2 mA	Published value
S	1600 μS	Published value
R _i	62.5 kΩ	Published value
μ	100	Published value

CAPACITANCE

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
c _{g/k}	1.6	Published value
c _a	0.4	Published value
c _{g/a}	1.7	Published value

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker