



ELECTRONIC TUBE REFERENCE

EEL71

Voltage - Tetrode electronic tube

CONSOLIDATED TECHNICAL DATA

2 SECTIONS

CONSTRUCTION

PENTODE-TETRODE

Combined tetrode and output-pentode tube for detector, AF preamplifier, and audio-output service. Its power pentode section gives the tube a clear output-stage function.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	8
NOMINAL HEATER	6.3 V / 750 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Dissimilar

SECTION RATINGS

SECTION1 Tetrode*No fixed ratings recorded.***SECTION2** Pentode

TRANSCONDUCTANCE	0.0065 S
MAXIMUM PLATE VOLTAGE	250 V
MAXIMUM SCREEN VOLTAGE	250 V
MAXIMUM CATHODE CURRENT	70 mA

Tetrode-output-pentode combination for detector, AF preamplifier and AF output service.

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker