



ELECTRONIC TUBE REFERENCE

EHA2500

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Forced-air-cooled transmitting triode designed for substantial radio-frequency amplifier or oscillator service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	8 V / 80 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
TRANSCONDUCTANCE	0.0055 S
AMPLIFICATION FACTOR	55
MAXIMUM PLATE VOLTAGE	7500 V
MAXIMUM PLATE DISSIPATION	2500 W

Forced-air-cooled transmitting triode for RF amplifier or oscillator service.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1960 Mazda

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 MAZDA

Section 1 · Triode

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum operating frequency	40 MHz	—

CONSTRUCTION

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Cooling method	Forced air	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker