

ELECTRONIC TUBE REFERENCE

F4108

Specialized - Traveling Wave electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
TRAVELINGWAVE

Water-cooled permanent-magnet Carcinotron backward-wave oscillator covering 90–100 GHz, with at least 100 mW millimeter-wave output.

GENERAL CHARACTERISTICS

BASE DESIGNATION	–	BASE PINS	–
NOMINAL HEATER	7 V / 2 A	PARALLEL HEATER	– / –
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1	TravelingWave
No fixed ratings recorded. Published source values promoted where applicable; additional electrical, RF, pulse and cooling data retained as parameters.	

Integral-magnet Carcinotron backward-wave oscillator covering 90–100 GHz with at least 100 mW output.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1958 Compagnie General

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1958 COMPAGNIE GENERAL

Section 1 · TravelingWave

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Frequency minimum	90 GHz	—
Frequency maximum	100 GHz	—
RF output minimum	100 mW	—

CONSTRUCTION

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Cooling method	Water	—
Focusing method	Permanent magnet	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker