



ELECTRONIC TUBE REFERENCE

F8072P2

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Thomson-CSF/Compagnie Générale P2 cathode-ray instrument tube for oscillographic or measurement display, with manufacturer-defined focusing, deflection, beam-control, and phosphor characteristics.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Cathode Ray*No fixed ratings recorded.**Cathode-ray display section.*

The F8072P2 is a 13 cm high-speed electrostatic-focus/electrostatic-deflection aluminized CRT, intended for high-speed professional or military oscilloscope/instrumentation service.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1958 Compagnie General

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1958 COMPAGNIE GENERAL

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	—
Heater Current	600 mA	—
Focusing Method	Electrostatic text	—
Deflection Method	Electrostatic text	—
Screen Construction	Aluminized text	—