



ELECTRONIC TUBE REFERENCE

F8076P2

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Thirteen-centimeter high-speed aluminized CRT with electrostatic focusing and electrostatic deflection. Compagnie Générale documentation identifies professional or military oscilloscope and instrumentation service across multiple phosphor variants.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Cathode Ray*No fixed ratings recorded.**Cathode-ray display section.*

The F8076P2 is a 13 cm high-speed electrostatic-focus/electrostatic-deflection aluminized CRT, intended for high-speed professional or military oscilloscope/instrumentation service.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1958 Compagnie General

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1958 COMPAGNIE GENERAL

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	—
Heater Current	600 mA	—
Focusing Method	Electrostatic text	—
Deflection Method	Electrostatic text	—
Screen Construction	Aluminized text	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker