



ELECTRONIC TUBE REFERENCE

F8081P7A

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

F8081-family electrostatic oscilloscope CRT with post-acceleration for professional instrumentation. Multiple phosphor and A-suffix variants provide different display persistence while retaining the same high-speed instrument function.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Cathode Ray*No fixed ratings recorded.**Cathode-ray display section with post-acceleration.*

The F8081P7A is an F8081-family electrostatic oscilloscope CRT with post-acceleration, intended for professional instrumentation.



SOURCE OPERATING CONDITIONS

1958 Compagnie General

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1958 COMPAGNIE GENERAL

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	—
Heater Current	600 mA	—
Focusing Method	Electrostatic text	—
Deflection Method	Electrostatic text	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum Post-Acceleration Voltage	13200 V	Grid7

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker