



ELECTRONIC TUBE REFERENCE

F9073

Specialized - Uncategorized electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

OTHER

Broadband electron-beam noise generator producing approximately 1 W integrated noise power across the 250–350 MHz band for measurement and calibration applications.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 2 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Other

No fixed ratings recorded.

Published ratings and characteristics promoted from the supplied CSF source where explicitly available.

Broadband electron-beam noise generator delivering about 1 W integrated noise power over 250–350 MHz.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1958 Compagnie General

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1958 COMPAGNIE GENERAL

Section 1 · Other

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	—
Heater Current	2 A	—
OperatingFrequencyMinimum	250 MHz	—
OperatingFrequencyMaximum	350 MHz	—
IntegratedNoisePower	1 W	—
Output Capacitance	3.5 pF	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
MaximumVoltage	1500 V	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker