

ELECTRONIC TUBE REFERENCE

FG67

Specialized - Thyatron electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
THYRATRON

Mercury-vapor thyatron for inverter circuits. Grid-controlled mercury discharge provides efficient electronic switching for power conversion.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	5 V / 4.5 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION0 Thyatron	
MAXIMUM PLATE VOLTAGE	1000 V
MAXIMUM CATHODE CURRENT	2.5 A
Thyatron. Forward peak anode maximum and average anode current promoted.	

The FG-67 is a mercury-vapor thyatron with an intermediate control characteristic, particularly designed for inverter circuits requiring short deionization time.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1968 General Electric Co

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1968 GENERAL ELECTRIC CO

Section 0 · Thyatron

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Peak Inverse Anode Voltage	1000 V	—
Instantaneous Anode Current	15 A	25CyclesAndAbove
Surge Anode Current	200 A	DesignOnly

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Peak Voltage Drop	16 V	Typical
Deionization Time	1000 us	Approximate

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker