



ELECTRONIC TUBE REFERENCE

G1051D

Voltage Regulator electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

VOLTAGEREGULATOR

Cold-cathode gas-filled voltage stabilizer for industrial and radio equipment, providing approximately 108 V over a 5-40 mA operating range.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	8
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Indirect; cold cathode	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Voltage Regulator	
REGULATOR VOLTAGE	108 V
MINIMUM REGULATOR CURRENT	5 mA
MAXIMUM REGULATOR CURRENT	40 mA
STARTING VOLTAGE	127 V
MAINTAINING VOLTAGE	108 V
Published ratings/characteristics promoted where applicable.	

Cold-cathode gas-filled voltage stabiliser for industrial and radio equipment.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1946 Standard Telephone and Cables

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1946 STANDARD TELEPHONE AND CABLES

Section 1 · Voltage Regulator

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum stabilising voltage at 40 mA	112 V	Published datasheet value
Maximum peak current	100 mA	Published datasheet value
Maximum regulation 5-40 mA	4 V	Published datasheet value

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Minimum stabilising voltage at 5 mA	105 V	Published datasheet value

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker