



ELECTRONIC TUBE REFERENCE

G7506D

Rectifier - Half Wave electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
RECTIFIER

Mercury-vapor half-wave rectifier for high-voltage industrial power conversion, using low arc voltage to provide efficient current handling in substantial DC supplies.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	2.5 V / 5 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Rectifier	
MAXIMUM CATHODE CURRENT	250 mA
PEAK INVERSE VOLTAGE	10000 V
NOMINAL OUTPUT CURRENT	250 mA
PEAK FORWARD CURRENT	1 A
FORWARD VOLTAGE DROP	15 V
WARM-UP TIME	12 s
<i>Mercury-vapour rectifier; average anode current used as nominal output current.</i>	

Directly heated mercury-vapour hot-cathode rectifier.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1953 AEG

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1953 AEG

Section 1 · Rectifier

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Filament voltage	2.5 V	—
Filament current	5 A	—
Peak inverse voltage	10 kV	—
Peak anode current	1 A	—
Average anode current	250 mA	—
Ignition voltage maximum	30 V	—
Warm-up time	12 sec	—

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Arc voltage drop	15 V	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker