

ELECTRONIC TUBE REFERENCE

GI37A

Power - Tetrode (NOT beam) electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
TETRODE

Russian pulse power tetrode; maximum anode voltage 15000 V.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 200 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION0	Tetrode
MAXIMUM PLATE VOLTAGE	15000 V
4 kW CW / 100 kW pulse; gm 0.055-0.075 A/V; filament 185-215 A; 500 MHz max.	



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

2026 Russian Power

Published test conditions and operating points. Values on this page are preserved as reported by this source.

2026 RUSSIAN POWER

Section 0 · Tetrode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater/filament voltage	6.3 V	Nominal heater/filament voltage
Heater/filament current	200 A	Nominal heater/filament current
Maximum plate voltage	15000 V	Maximum anode voltage; continuous rating unless pulse qualification specified

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Center/operating frequency	500 MHz	Maximum operating frequency stated by manufacturer; not a typical center frequency

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker