

ELECTRONIC TUBE REFERENCE

GI43A

Power - Tetrode (NOT beam) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TETRODE

Russian pulse power tetrode; maximum anode voltage 25000 V.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	7.5 V / 390 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION0	Tetrode
MAXIMUM PLATE VOLTAGE	25000 V
15 kW CW / 500 kW pulse; gm 0.090-0.130 A/V; filament 360-420 A; 500 MHz max.	



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

2026 Russian Power

Published test conditions and operating points. Values on this page are preserved as reported by this source.

2026 RUSSIAN POWER

Section 0 · Tetrode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater/filament voltage	7.5 V	Nominal heater voltage
Heater/filament current	390 A	Nominal heater current
Maximum plate voltage	25000 V	Maximum anode voltage

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Center/operating frequency	500 MHz	Maximum operating frequency stated by manufacturer; not a typical center frequency

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker