

ELECTRONIC TUBE REFERENCE

GL8008

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

High-power RF triode for oscillator, amplifier, or transmitting service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	4.75 V / 5 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode
No fixed ratings recorded. Promoted fields mapped from printed ratings/characteristics headings; specialized published data retained in parameter rows.

High-power transmitting triode.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1968 General Electric Co

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1968 GENERAL ELECTRIC CO

Section 1 · Triode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
ETI	-256 A	ETI-256A
Cathode heating timerequired	30 seconds	Cathode heating timerequired 30 seconds
ETI	-256 A	ETI-256A
Mazximum averaging time. 15	15 seconds	Mazximum averaging time. 15 15 seconds