



ELECTRONIC TUBE REFERENCE

GL866A

Rectifier - Half Wave electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
RECTIFIER

Mercury-vapor half-wave rectifier for high-voltage industrial power conversion, using low arc voltage to provide efficient current handling in substantial DC supplies.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	2.5 V / 5 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Rectifier	
PEAK INVERSE VOLTAGE	10000 V
NOMINAL OUTPUT CURRENT	500 mA
PEAK FORWARD CURRENT	1 A
FORWARD VOLTAGE DROP	15 V
WARM-UP TIME	30 s

Half-wave mercury-vapor rectifier designed for high peak inverse voltage and low forward drop.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1968 General Electric Co

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1968 GENERAL ELECTRIC CO

Section 1 · Rectifier

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heating Time	30 s	Typical

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
MaximumInstantaneousAnodeCurrent	1 A	At10000VPIV
DC Output Voltage	3180 V	FullWave;ChokeInputFilter;TwoTubes
DC Output Current	500 mA	FullWave;ChokeInputFilter;TwoTubes

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker