ELECTRONIC TUBE REFERENCE

GMI26B

Specialized - Switching Tube electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
TETRODE

Russian high-voltage pulse tetrode for modulator switching.

General characteristics

BASE DESIGNATION	—	**BASE PINS**	—
NOMINAL HEATER	12.6 V / 5.5 A	**PARALLEL HEATER**	— / —
HEATING	Indirect	**SERIES OPERATION**	Not specified
CATHODE ARRANGEMENT	Separate cathodes	**SECTION CONSTRUCTION**	Similar

Section ratings

SECTION0 Tetrode

MAXIMUM PLATE VOLTAGE	10000 V

Pulse switching/modulator service; maximum pulse duration 30 microseconds. Output power is not plate dissipation.

SOURCE OPERATING CONDITIONS

2026 Russian Power

SOURCE PDF

Published test conditions and operating points. Values on this page are preserved as reported by this source.

2026 RUSSIAN POWER

Section 0 · Tetrode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater/filament voltage	12.6 V	Nominal heater voltage
Heater/filament current	5.5 A	Nominal heater current
Maximum plate voltage	10000 V	Maximum anode voltage
Maximum pulse duration	30 µs	Maximum pulse duration as stated in manufacturer mini-datasheet

Tube Tinker

An independent reference for electronic tubes, vacuum tubes, and their source documents.

Catalog Tube types Full books Blog Feedback & corrections

© 2026 Tube Tinker