ELECTRONIC TUBE REFERENCE

GMI29A1

Specialized - Switching Tube electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
TETRODE

> Russian high-voltage pulse tetrode for modulator switching.

General characteristics

BASE DESIGNATION	—	**BASE PINS**	—
NOMINAL HEATER	12.6 V / 69.5 A	**PARALLEL HEATER**	— / —
HEATING	Indirect	**SERIES OPERATION**	Not specified
CATHODE ARRANGEMENT	Separate cathodes	**SECTION CONSTRUCTION**	Similar

Section ratings

SECTION0 Tetrode

MAXIMUM PLATE VOLTAGE	40000 V

Pulse switching/modulator service; maximum pulse duration 10 microseconds. Output power is not plate dissipation.

SOURCE OPERATING CONDITIONS

2026 Russian Power

SOURCE PDF

Published test conditions and operating points. Values on this page are preserved as reported by this source.

2026 RUSSIAN POWER

Section 0 · Tetrode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater/filament voltage	**12.6 V**	Nominal heater voltage
Heater/filament current	**69.5 A**	Nominal heater current
Maximum plate voltage	**40000 V**	Maximum anode voltage
Maximum pulse duration	**10 µs**	Maximum pulse duration as stated in manufacturer mini-datasheet

Tube Tinker

An independent reference for electronic tubes, vacuum tubes, and their source documents.

Catalog Tube types Full books Blog Feedback & corrections

© 2026 Tube Tinker