



ELECTRONIC TUBE REFERENCE

H141D

Voltage - Triode (under 100V) electronic tube

CONSOLIDATED TECHNICAL DATA

2 SECTIONS

CONSTRUCTION

DIODE-TRIODE

Dry-cell battery diode-triode combining a detector diode with a triode amplifier for portable receiving equipment.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	1.4 V / 50 mA	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Dissimilar

SECTION RATINGS

SECTION1 Diode

No fixed ratings recorded.

SECTION2 Triode

PLATE RESISTANCE	135000 Ω
TRANSCONDUCTANCE	0.00048 S
AMPLIFICATION FACTOR	65
MAXIMUM PLATE VOLTAGE	90 V

Dry-cell battery single-diode triode.

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker