

ELECTRONIC TUBE REFERENCE

HMI951

Specialized - Magnetron electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
MAGNETRON

High-power X-band pulse magnetron designed for radar-generator service around 9.345-9.405 GHz.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 1 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Magnetron	
MAXIMUM PLATE VOLTAGE	14000 V
MAXIMUM CATHODE CURRENT	16 A
Magnetron interaction-space system; RF frequency, output power and pulse/CW limits captured as parameters.	

High-power pulse magnetron for radar-generator service in the 9345 to 9405 MHz band.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1953 RFT Rundfunk Technik

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1953 RFT RUNDFUNK TECHNIK

Section 1 · Magnetron

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
HeaterVoltageNominal	6.3 V	Nominal
HeaterCurrentNominal	1 A	Nominal
Maximum Peak Anode Voltage	14000 V	—
Maximum Peak Anode Current	16 A	—
PulseInputPowerMaximum	200000 W	—
MaximumPulseDuration	2.5 us	—

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
FrequencyRange	9.345–9.405 GHz	Published operating range
RFOutputPower	45000 W	Pulse

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker