

ELECTRONIC TUBE REFERENCE

IN15A

Nixie electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
NIXIE

Russian cold-cathode symbol display intended for visual indication of electrical or operating-state symbols rather than ordinary numerical digits.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Indirect; cold cathode	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Nixie	
MAXIMUM REGULATOR CURRENT	2.5 A
STARTING VOLTAGE	170 V
Single cold-cathode glow-discharge indicator section; Nixie-specific operating data are also retained as parameters.	

The IN15A is a Russian cold-cathode glow-discharge Nixie numeric/symbol display intended for visual indication. Ignition voltage up to 170 v, published life at least 1000 h. The supplied Russian datasheet was translated for this record.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

196X Nixie Russian 2

Published test conditions and operating points. Values on this page are preserved as reported by this source.

196X NIXIE RUSSIAN 2

Section 1 · Nixie

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Indication current	—2.5 mA	Published datasheet value
DC operating current	—3.5 mA	Published datasheet value
Ambient operating temperature minimum	-60 degC	Published datasheet value
Ambient operating temperature maximum	70 degC	Published datasheet value
Supply voltage	200— V	Minimum stated source/supply voltage
Ignition voltage	—170 V	Published datasheet value
Indication current	—2.5 mA	Published datasheet value

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Service life	1000— h	Minimum

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker